
POPPY LED 1500 6500 840/65 E2 96651740

LED batten

A fast install and versatile IP20 batten with press release buttons for quick opening and installation. Vario dual switchable light colour: choose between cool white (4000 K) or daylight (6500 K). Reliable integrated LED technology, ensuring maintenance-free installation and a long lifetime. Homogeneous illumination. Direct replacement for conventional battens in terms of light performance and length. Piano-key terminals, enabling loop-in loop-out. RCM certified driver. 2 hour emergency lighting. Body: sheet metal, white finish (RAL 9002). Diffuser: polycarbonate, opal. End caps: polycarbonate, white (RAL 9002). Weight: 4.3 kg




TE_POPPY_F_persp.jpg



TE_POPPY_M_1500.wmf

Light Distribution STD - standard



TE_POPPY_VARIO_PAC_1500_6500_840_E2.ldt

- Light Source: LED
- Luminaire luminous flux*: 6600 lm
- Luminaire efficacy*: 120 lm/W
- Colour Rendering Index min.: 80
- Correlated colour temperature*: 4000-6500 Kelvin
- Chromaticity tolerance (initial MacAdam): 5
- Rated median useful life*:
  L70 50000 h at 25 °C
- Ballast: 1x LED_Con
- Luminaire input power*: 55 W Power factor = 0.9
- Dimming: Fixed output
- Maintenance category CIE 97: D - Enclosed IP2X
- Total harmonic distortion (THD): 15.00 %

All values marked with an * are rated values. Connected electrical load and luminous flux are subject to an initial tolerance of +/- 10%, the most similar colour temperature is subject to an initial tolerance of +/- 150K. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

RoHS IP20 IK08 850°C T_a 0 +25

We reserve the right to make technical changes without prior notice. 28.03.2024 © ThornEco